

Impact Plus M2 | 2 m

Product numberD1C9254Weight0.15kgLength55mmWidth250mmHeight145mm



Product description

High-quality components like the inner conductor made from oxygen-free copper and the triple shielding are guarantees for interference-free signal transmission between two devices with mini-display port connections. The highly flexible and also tough cable with its plastic sheathing achieves data transmission rates of up to 25.92 Gbit/s and maximum resolution of 5120 x 2880 pixels. Thanks to its 24-carat gold-plated contacts and a solid plastic connector plug with a metal housing, the Impact Plus M2 ensures perfect contact reliability and signal stability.

24kt gold plated contacts, 20-pin plug, Resolution up to 5K (5120x2880), Reliable contact, Data transmission

Product properties

Inner conductor

material

Features

OFC - oxygen-free copper

25.92 Gbits/s

25.92 Gbits/s / 810 Mhz, Supports HDCP and DPCP, 30 years warranty**

Product Category Data cable

Plug type 2 Mini-Displayport

Colour Black

Shielding triple shielding

cable length 2 m

Surface condition 24 carat gold-plated contacts

Shielding construction

2 x aluminium foil + 1 x copper braiding

CONSTRUCTION

Connection typeDataQuality levelExcellenceSignal directionIN/OUT

Plug type 1 Mini display port



More images







