



# Optosel 4:1 MKII

<b>Product number</b>	D1C6041
<b>Weight</b>	0.38kg
<b>Length</b>	145mm
<b>Width</b>	120mm
<b>Height</b>	30mm



## Product description

The Oehlbach Optosel 4:1 MKII (successor of the Optosel 4:1) receives up to four digital optical signals and transmits them unprocessed to an AV receiver. The switch box is perfectly suited in combination with AV receivers that only offer a single TOSLINK slot. The device, which sits in a solid metal housing, supports sampling rates and a resolution of up to 192 kHz / 24 bit. A high-quality and loss-free signal transmission is thus guaranteed. Both compressed and uncompressed audio signals are supported. A remote control for the comfortable change of the inputs is included in the scope of delivery as well as a power supply unit.

## Product properties

<b>Audio format</b>	DTS-HD Master Audio, Dolby Digital, DTS:X, Dolby TrueHD, DTS HD, LPCM, Dolby Atmos
<b>Housing material</b>	Ultra thin single conductors
<b>Bit depth</b>	24Bit
<b>Plug type 2</b>	TOSLINK
<b>Connection type</b>	Audio
<b>Plug type 1</b>	TOSLINK
<b>Sampling rate</b>	192 KHz
<b>Quality level</b>	Excellence
<b>Product Category</b>	Electronics
<b>Signal direction</b>	OUT
<b>Colour</b>	Metallic Brown
<b>Temperature range:</b>	0°C-40°C



More images

