



SIGNAL DIRECTION



EXCELLENT BI-WIRING SPEAKER CABLE

BI-TECH 4

2X2,5MM² + 2X4,0MM²

MSRP (19%): 50.49

Outstanding bi-wiring speaker cable of the extra class. 2 x 2.5 mm² silver-plated oxygen-free copper for the mids / highs and 2 x 4 mm² oxygen-free copper for the loss-free transmission of the bass. It reproduces an impressively natural and detailed sound image. The use of very high quality materials for both the conductors and the insulation ensure high flexibility and guarantee excellent, powerful bass with fine-detailing treble at the same time.

» 350 W

MADE IN
EUROPE

OFC
OXYGEN-FREE
COPPER

SPOFC
SILVER-PLATED
COPPER

Packaging size	215mm / 375mm / 375mm
Weight (net)	200 g
Inner conductor material	SPC/OFC - silver-plated oxygen-free copper, OFC - oxygen-free copper
cable geometry	Round
cable cross section	2 x 2.5 mm ² + 2 x 4.0 mm ²
power max.	For amplifier performances of up to 350 watts
Scope of delivery	Loudspeaker cables, info brochure
Features	Certified production in Europe
Outer sheath material	plastic

item no.	Length	EAN	MSRP (19%)
1080	50 m	4003635010808	50.49 €

Item No. 1080

