





**BI-WIRING** 

Pre-assembled with Oehlbach Fusion cable lug connectors, this top-class bi-wiring speaker cable continues to set standards in terms of high-fidelity sound characteristics.

It has been specially tuned for hi-fi purists and, in addition to a sophisticated technical concept, also offers a particularly unique product design.

The material of the inner conductor consists of the high-purity and absolutely oxygen-free HPOCC copper. This unique manufacturing process achieves almost monocrystalline transitions within the copper.

The cable construction is based on the consistent separation of the signal paths for the high and low frequency range and achieves a unique transmission quality. Thus, 12 individually insulated copper strands were additionally wrapped with a wafer-thin copper foil. This unique concept in cable construction requires tremendous manufacturing precision with the main goal of achieving a delay correction between the high and low frequencies.

The low frequencies prefer the more solid inner conductor, while high frequencies tend to travel on the surface and have a higher velocity. The combination of inner conductor and foil results in an unprecedented natural and dynamic sound image.

HPOCC®	FULL	30 YEAR	MADE IN	<b>24ct</b>
INSIDE	Metal	GUARANTEE	Germany	GOLD

Connector material	solid metal plug	
Inner conductor material	HPOCC® – mono-crystalline oxygen-free copper inner conductor	
cable geometry	Round	
Features	Stereo speaker cable , 30 years warranty, Rigorous separation of signal routes, Made in Germany, 24kt gold plated contacts	
cable material	fabric sheath	
Cable diameter	13 mm	

item no.	Length	Color	EAN	MSRP (19%)
14220	2 m	Black	4003635142202	1020.00€
14221	2.50 m	Black	4003635142219	1140.00€
14222	3 m	Black	4003635142226	1260.00 €
14231	3.50 m	Black	4003635142318	1559.00€
14232	4 m	Black	4003635142325	1679.00€
14233	4.50 m	Black	4003635142332	1799.00€
14234	5 m	Black	4003635142349	1919.00 €







2 x cable 4 x cable shoe lug 2x X 4 X X SIGNAL DIRECTION

Uni-Directorate

