









4 x cable lug

4x**€**

SIGNAL DIRECTION



Uni-Directorate



HIGH END SPEAKER CABLE SET WITH CABLE LUGS

FUSION FOUR.4

BI-AMPING

This extra-class bi-amping loudspeaker cable preassembled with "Fusion" lugs continues to set standards for high-fidelity sound. This cable has been specially designed with hi-fi purists in mind and it offers a sophisticated technical concept in addition to a particularly discrete product design. The material used for the inner conductor consists of high-purity, oxygen-free HPOCC copper. Monocrystalline-like transitions are achieved within the copper thanks to the unique HPOCC manufacturing process applied. The cable has been structured to rigorously separate the treble and bass transmission routes and thus achieves a unique quality of transmission. Each of the twelve individually insulated copper wires has been wrapped in wafer-thin copper foil. This unique concept in cable construction requires a tremendous degree of precision in the manufacturing process with the main aim of achieving a time delay correction between the high and low frequencies. The low frequencies prefer the more solid inner conductor while the high frequencies tend to move along the surface at greater speeds. The combination of the inner conductor and foil results in an unprecedented natural and dynamic sound.











Connector material	solid metal plug		
Inner conductor material	HPOCC® – mono-crystalline oxygen-free copper inner conductor		
cable geometry	Round		
Features	Bi-amping loudspeaker cable, 24kt gold plated contacts , Rigorous separation of signal routes, Made in Germany, Stereo speaker cable , 30 years warranty		
cable material	fabric sheath		
Cable diameter	13 mm		

item no.	Length	Color	EAN	MSRP (19%)
14320	2 m	Black	4003635143209	1140.00 €
14321	2.50 m	Black	4003635143216	1260.00 €
14322	3 m	Black	4003635143223	1380.00 €
14330	3.50 m	Black	4003635143308	1559.00 €
14331	4 m	Black	4003635143315	1679.00 €
14332	4.50 m	Black	4003635143322	1799.00 €
14333	5 m	Black	4003635143339	1919.00 €