



Toslink



DIGITAL OPTICAL SWITCH

OEHLBACH OPTOSEL 4:1

96 KHZ

MSRP (19%): 109.00

The Oehlbach Optosel 4:1 receives up to four digital optical signals and forwards them unprocessed to an AV receiver. The switch box is perfectly suited in combination with AV receivers that only offer a single TOSLINK slot. The device, which is housed in a solid metal case, supports sampling rates and a resolution of up to 96kHz/24-bit. A high-quality and loss-free signal transmission is therefore absolutely guaranteed. Both compressed and uncompressed audio signals are supported. A remote control for the comfortable change of the inputs is included in the scope of delivery as well as a power supply unit.

DTS:X
**DOLBY
ATMOS**
DTS HD
**DOLBY
TRUE HD**
**DOLBY
DIGITAL**
DTS
LPCM

| | |
|--------------------|--|
| Packaging size | 55mm / 165mm / 230mm |
| Weight (net) | 133 g |
| Colour | Metallic Brown |
| Housing material | Ultra thin single conductors |
| Scope of delivery | Digital distributor, power supply unit, remote control, operating instructions |
| Air humidity range | 20 - 90 % |
| Audio format | Dolby Atmos, DTS:X, Dolby Digital, DTS-HD Master Audio, Dolby True HD, Controle LED, LPCM, DTS HD, Dolby TrueHD, DTS, 5.1 DTS HD |
| Sampling rate | >96 kHz |
| Article width | 94 mm |
| Article height | 24 mm |
| Article depth | 83 mm |
| Input voltage | 5 V |
| Input power | 5 W |
| Input current | 1 A |

| item no. | Color | EAN | MSRP (19%) |
|----------|----------------|---------------|------------|
| 6040 | metallic brown | 4003635060407 | 109.00 € |

Item No. 6040



More information:

