



## DIGITAL-OPTICAL AUDIO SWITCH

### OPTOSEL 4:1 MKII

192 KHZ

**MSRP (19%): 88.00**

The Oehlbach Optosel 4:1 MKII (successor of the Optosel 4:1) receives up to four digital optical signals and transmits them unprocessed to an AV receiver. The switch box is perfectly suited in combination with AV receivers that only offer a single TOSLINK slot. The device, which sits in a solid metal housing, supports sampling rates and a resolution of up to 192 kHz / 24 bit. A high-quality and loss-free signal transmission is thus guaranteed. Both compressed and uncompressed audio signals are supported. A remote control for the comfortable change of the inputs is included in the scope of delivery as well as a power supply unit.

**DTS:X**

**192 kHz  
24 Bit**

**DOLBY  
ATMOS**

**DTS HD**

**DOLBY  
TRUE HD**

**DOLBY  
DIGITAL**

**LPCM**



Toslink



SIGNAL DIRECTION



Packaging size	45.00mm / 140.00mm / 225.00mm
Weight (net)	135 g
Colour	Metallic Brown
Housing material	Ultra thin single conductors
Scope of delivery	Digital switcher, user manual, power supply, remote control
Air humidity range	20 - 90 %
Audio format	LPCM, DTS HD, DTS:X, Dolby TrueHD, Dolby Digital, DTS-HD Master Audio, Dolby Atmos
Sampling rate	192 KHz
Article width	94 mm
Article height	24 mm
Article depth	83 mm
Input voltage	5 V
Input power	5 W
Input current	1 A



item no.	Color	EAN	MSRP (19%)
6041	metallic brown	4003635060414	88.00 €

Item No. 6041

