



Terminal



SIGNAL DIRECTION



Bi-Directional

SPEAKER CABLES

SPEAKER WIRE 40

2 X 4.0 MM²

High-quality stereo loudspeaker cable. This loudspeaker cable is suitable for amplifier performances of up to around 180 watts of power per amplifier channel. This Oehlbach cable's outer sheath consists of a tough and flexible mix of plastics. At the same time, the inner conductor is made up of many individual wires that in turn have been twisted together to form bundles and thus produce a cable, which is extremely flexible and thus easy to lay.

» 180 W

MADE IN
EUROPE

OFC
OXYGEN-FREE
COPPER

30 YEAR
GUARANTEE

Bending radius	25 mm
Inner conductor material	OFC - oxygen-free copper
cable geometry	Flat, Individually stranded strand bundles
cable cross section	2 x 4.0 mm ²
power max.	For amplifier performances of up to 180 watts
Ladder construction	(68 x 0.10mm) x 7
Features	Certified production in Europe, Stereo speaker cable , 30 years warranty
cable material	plastic

item no.	Length	Color	EAN	MSRP (19%)
1010	100 m	Crystal clear	4003635010105	9.99 €
1042	250 m	Crystal clear	4003635010426	9.99 €
1053	100 m	White	4003635010532	9.99 €

More information:

