



Terminal



SIGNAL DIRECTION



## SPEAKER CABLES

### SPEAKER WIRE SP-25

2 X 2.5 MM<sup>2</sup>

Excellently made stereo loudspeaker cable wound on to a mini coil. This loudspeaker cable is suitable for amplifier performances of up to around 120 watts of power per amplifier channel. The use of oxygen-free copper (OFC) as the conducting material ensures that an extremely clear and true-to-life sound can be achieved with this loudspeaker cable. The cable has also been made from very many ultrathin stranded copper wires – each individual wire possesses a cross-section of around 0.125 mm. This complex design means that the cable is particularly conductive and flexible throughout.

**120 W**

**OFC**  
OXYGEN-FREE  
COPPER

**30 YEAR  
GUARANTEE**

Bending radius	18 mm
Inner conductor material	OFC - oxygen-free copper
cable geometry	Round
cable cross section	2 x 2.5 mm <sup>2</sup>
power max.	For amplifier performances of up to 120 watts
Features	Stereo speaker cable , 30 years warranty
cable material	plastic

item no.	Length	Color	EAN	MSRP (19%)
102	10 m	Crystal clear	4003635001028	39.99 €
106	20 m	Crystal clear	4003635001066	65.99 €
108	30 m	Crystal clear	4003635001080	96.00 €
192	10 m	White	4003635001929	39.99 €
196	20 m	White	4003635001967	65.99 €
198	30 m	White	4003635001981	96.00 €

