



Terminal



SIGNAL DIRECTION



## SPEAKER CABLES

### SPEAKER WIRE SP-40

2 X 4.0 MM<sup>2</sup>

Excellently made stereo loudspeaker cable wound on to a mini coil. This loudspeaker cable is suitable for amplifier performances of up to around 180 watts of power per amplifier channel. The use of oxygen-free copper (OFC) as the conducting material ensures that an extremely clear and true-to-life sound can be achieved with this loudspeaker cable. The cable has also been made from very many ultrathin stranded copper wires – each individual wire possesses a cross-section of around 0.10 mm. This complex design means that the cable is particularly conductive and flexible throughout.

180 W

OFC  
OXYGEN-FREE  
COPPER

30 YEAR  
GUARANTEE

Bending radius	25 mm
Inner conductor material	OFC - oxygen-free copper
cable geometry	Round
cable cross section	2 x 4.0 mm <sup>2</sup>
power max.	For amplifier performances of up to 180 watts
Features	30 years warranty, Stereo speaker cable
cable material	plastic

item no.	Length	Color	EAN	MSRP (19%)
301	10 m	transparent	4003635003015	71.99 €
302	20 m	transparent	4003635003022	119.00 €
305	30 m	transparent	4003635003053	215.00 €
306	10 m	White	4003635003060	71.99 €
307	20 m	White	4003635003077	119.00 €
308	30 m	White	4003635003084	215.00 €

